

# BOSS DRYING AGENT CONCENTRATE


PRODUCT CODE 9441

**ADVANTAGES:**

- Provides quick drying results
- Provides increased protection
- Improves shine & water repellency
- Assists in eliminating water spotting

**AVANTAGES:**

- Fournit des résultats de séchage rapide
- Fournit une protection accrue
- Améliore la brillance et imperméabilité à l'eau
- Aide à éliminer les taches d'eau

<p><b>DANGER</b> Highly flammable liquid and vapour Causes skin irritation Causes serious eye irritation</p> <p>Keep container tightly closed Ground/bond container and receiving equipment Use explosion-proof electrical/ventilating/light/equipment Use only non-sparking tools Take precautionary measures against static discharge Wash exposed areas thoroughly after handling Wear protective gloves/protective clothing/eye protection/face protection Specific treatment (see section 4 of SDS) Take off contaminated clothing and wash before reuse</p> <p>In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide for extinction Store in a well ventilated place. Keep cool Dispose of contents/container in accordance with local regulation</p> <p><b>FIRST AID</b> <b>If swallowed:</b> Rinse mouth. Do NOT induce vomiting. Immediately call a poison center or doctor/physician. <b>If on skin (or hair):</b> Immediately take off all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs get medical advice/attention. Wash contaminated clothing before reuse. <b>If inhaled:</b> Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor/physician if you feel unwell. <b>If in eyes:</b> Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a doctor/physician.</p>		<p><b>DANGER</b> Liquide et vapeurs très inflammables Provoque une irritation cutanée Provoque une sévère irritation des yeux</p> <p>Maintenir le récipient fermé de manière étanche Mise à la terre/liaison équipotentielle du récipient et du matériel de réception Utiliser du matériel électrique/de ventilation/d'éclairage/antidéflagrant Ne pas utiliser d'outils produisant des étincelles Prendre des mesures de précaution contre les décharges électrostatiques Se laver les zones exposées soigneusement après manipulation Porter des gants de protection/des vêtements de protection/un équipement de protection des yeux/du visage Traitement spécifique (voir la section 4 du FDS) Enlever les vêtements contaminés et les laver avant réutilisation En cas d'incendie : Utiliser de l'eau pulvérisée, de la mousse résistante à l'alcool, poudre chimique ou du dioxyde de carbone pour l'extinction Stocker dans un endroit bien ventilé. Tenir au frais. Éliminer le contenu / récipient conformément à la réglementation locale</p> <p><b>PREMIERS SOINS</b> <b>En cas d'ingestions :</b> Rincer la bouche. Ne PAS faire vomir. Appeler immédiatement un centre antipoison ou un médecin. <b>En cas de contact avec la peau (ou les cheveux) :</b> Enlever immédiatement les vêtements contaminés. Rincer la peau à l'eau/se doucher. En cas d'irritation cutanée: consulter un médecin. Laver les vêtements contaminés avant réutilisation. <b>En cas d'inhalation :</b> Transporter la victime à l'extérieur et la maintenir au repos dans une position où elle peut confortablement respirer. Appeler immédiatement un centre antipoison ou un médecin. <b>En cas de contact avec les yeux :</b> Rincer avec précaution à l'eau pendant plusieurs minutes. Enlever les lentilles de contact si la victime en porte et si elles peuvent être facilement enlevées. Continuer à rincer. Appeler immédiatement un centre antipoison ou un médecin.</p>
--	---	---



# BOSS DRYING AGENT CONCENTRATE / CONCENTRÉ

*A clear liquid which provides superior beading action on vehicle surfaces, causing rapid drying.  
Provides a lustrous protective coating on the automobile that inhibits rust formation.*

*Un liquide clair qui fournit une action de perlage supérieure sur les surfaces du véhicule, provoquant un séchage rapide. Fournit un revêtement protecteur lustré sur l'automobile qui inhibe la formation de rouille.*

PSL1427A  
BOX9441



Net Contents / Contenu Net  
**18.9 L**

PSL 1427A

ART #:CHA 816	DESIGNER #: AT	NOTE:
---------------	----------------	-------

CLIENT: CHARLOTTE	JOB DESCRIPTION: PSL 1427A BOSS Drying Agent	DATE: OCTOBER 16, 2018	PROOF# <b>3</b>
-------------------	--	------------------------	-----------------



LABEL SIZE  
7" x 7.75"  
DIE# R888  
ROLL DIRECTION  




**THE CLIENT IS RESPONSIBLE FOR APPROVING THE FOLLOWING:**

1. ALL COPY
2. LABEL DIMENSIONS
3. COLOURS USED
4. REWIND COPY DIRECTION
5. LOCAL, PROVINCIAL OR NATIONAL REGULATIONS ASSOCIATED WITH THIS LABEL(S)

APPROVED AS IS : \_\_\_\_\_

APPROVED WITH CHANGES INDICATED : \_\_\_\_\_

RE-PROOF  DATE : \_\_\_\_\_

**MATERIAL:**  
WHITE PAPER

**COATING:**  
GLOSS LAMINATE

**THIS IS NOT A COLOUR ACCURATE PROOF.**  
Please refer to process and pantone colour charts for accurate colour representation. Every effort has been made to ensure the accuracy of this proof. However, the client is responsible for ensuring that label size, copy, graphics and colour separations are accurate, and to notify Perflex Label Inc. of any discrepancies prior to film, plate or label production. The client indemnifies Perflex Label Inc. against any liability related to costs incurred due to errors on a customer signed proof.

